

Specifications

Model	Nominal Voltage	Nominal Capacity	Dimension		Weight Approx
	V		mAh	Diameter(mm±0.3)	Height(mm ± 0.3)
32131	3.2	12800	32	120	250
32135	3.2	15000	32	135	270
34600C	3.7	7000	34.3	60.2	150
32650C	3.7	6500	32.3	65.2	137
32600C	3.7	5500	32.5	60.2	125
32550C	3.7	5000	32.5	60.2	118
26650C	3.7	5000	26.3	65.2	90
26650C	3.7	4500	26.3	65.2	88
26500C	3.7	3200	26.3	50.2	66
26350C	3.7	2000	26.3	35.2	45.8
22650C	3.7	3000	22.3	65.2	63.5
22500C	3.7	2400	22.3	50.2	49.8
22430C	3.7	2000	21.5	43.2	43
21700C	3.7	4200	21.5	70.2	73.5
18650C	3.7	2600	18.5	65.2	46.5
18650C	3.7	2500	18.5	65.2	45.5
18650C	3.7	2400	18.5	65.2	44
18650C	3.7	2200	18.5	65.2	41.5
18650C	3.7	2000	18.5	65.2	42.8
18650C	3.7	1800	18.5	65.2	41
18650C	3.7	1500	18.3	65.5	40.6
18650C	3.7	1300	18.3	65.2	38.5
18620C	3.7	2000	18.3	65.2	42
18500C	3.7	1900	18.3	50.2	35.2
18500C	3.7	1600	18.3	50.2	34.2
18500C	3.7	1500	18.3	50.2	33
18500C	3.7	1400	18.3	50.2	32
18500C	3.7	1200	18.3	50.2	32
18350C	3.7	850	18.3	35.2	21.5
16650C	3.7	1800	16.3	65.2	36.0
16500C	3.7	1200	16.8	50.2	27.5
16500C	3.7	1000	16.8	50.2	26.5

Specifications

Model	Nominal Voltage	Nominal Capacity	Dimension		Weight Approx
	V	mAh	Diameter(mm±0.3)	Height(mm ± 0.3)	g ± 2
16340C	3.7	700	16.8	34.0	17
16280C	3.7	550	16.8	28.0	14.0
16310C	3.7	650	16.8	31.0	14.5
14650C	3.7	1200	14.2	65.2	25
14650C	3.7	1000	14.2	65.2	24
14500C	3.7	800	14.2	50.2	20.2
14500C	3.7	700	14.2	50.2	18.5
14500C	3.7	650	14.2	50.2	17
14500C	3.7	600	14.2	50.2	20
14430C	3.7	650	14.2	43.0	16.5
14430C	3.7	600	14.2	43.0	16.2
14430C	3.7	550	14.2	43.0	16
14280C	3.7	320	14.2	28.0	10.5
14200C	3.7	150	14.2	20.0	8
10840C	3.7	600	10.3	84.0	17
10440C	3.7	320	10.3	44.0	8
10150C	3.7	80	10.3	15.0	5
10870C	3.7	750	10.3	87.0	17.5
10380C	3.7	250	10.3	38.0	8
10180C	3.7	100	10.3	18.0	5
16650C	3.7	1600	16.3	65.2	34
16310C	3.7	750	16.8	31.0	16
16310C	3.7	700	16.8	31.0	15.5
26650MP	3.7	4200	26.3	65.2	87
21700MP	3.7	4000	21.3	70.0	69.8
18650MP	3.7	2500	18.5	65.2	45
18650MP	3.7	2200	18.5	65.2	44.5
18650MP	3.7	2000	18.5	65.2	41
18650MP	3.7	1500	18.3	65.2	41
18650NP	3.7	1900	18.5	65.2	34.8
18650NP	3.7	1500	18.3	65.2	39.2
26650HP	3.7	3400	26.5	65.2	84.2
26500HP	3.7	2000	26.3	50.2	63

Specifications

Model	Nominal Voltage	Nominal Capacity	Dimension		Weight Approx
	V		mAh	Diameter(mm±0.3)	
22650HP	3.7	2000	23.5	65.2	56
21700HP	3.7	3000	21.5	70.0	61.8
18650HP	3.7	2500	18.5	65.2	41.0
18650HP	3.7	2200	18.5	65.2	40.0
18650HP	3.7	2000	18.5	65.2	42.5
18650HP	3.7	1500	18.3	65.2	40.2
18650HP	3.7	1300	18.3	65.2	38.0
18500HP	3.7	1100	18.3	50.2	32
18350HP	3.7	700	18.3	35.0	21.5
16500HP	3.7	800	16.8	50.2	26
16340HP	3.7	600	16.8	34.0	16.5
14650HP	3.7	900	14.2	65.2	26.2
14500HP	3.7	650	14.2	50.2	19.5
26650C	3.2	3000	26.0	65.0	81
18650C	3.2	1500	18.0	65.0	39
18500C	3.2	1000	18.0	50.0	32
14500C	3.2	500	14.0	50.0	20
14430C	3.2	400	14.0	43.0	17.5
12360HP	3.2	240	12.0	37.0	8
10370HP	3.2	140	10.3	37.0	6

Temperature Battery

Model	Nominal Voltage	Nominal Capacity	Dimension		Weight Approx
	V		mAh	Diameter(mm±0.3)	
18650T	3.7	2500	18.3	65.2	45
18650T	3.7	2000	18.3	65.2	42.9
14500T	3.7	600	14.2	50.2	19.1
14250T	3.7	250	14.2	25.0	9.2
14200T	3.7	200	14.2	20.0	8
10380T	3.7	200	10.2	38.0	7

Specifications

Model	Nominal Voltage	Nominal Capacity	Dimension		Weight Approx
	V	mAh	Diameter(mm±0.3)	Height(mm ± 0.3)	g ± 2

Low Temperature Battery

Model	Nominal Voltage	Nominal Capacity	Dimension		Weight Approx
	V	mAh	Diameter(mm±0.3)	Height(mm ± 0.3)	g ± 2
18650L	3.7	2600	18.0	65.2	45.5
18650L	3.7	2200	18.0	65.2	42

Low Temperature & Power Battery

Model	Nominal Voltage	Nominal Capacity	Dimension		Weight Approx
	V	mAh	Diameter(mm±0.3)	Height(mm ± 0.3)	g ± 2
18650LP	3.7	2500	18.0	65.2	45
18350LP	3.7	850	18.0	35.2	21